

ergotron®

moving you forward

Neo-Flex® WideView WorkSpace Neo-Flex® Dual WideView WorkSpace

- Flexible, open-architecture design is scalable for future videoconferencing or computer equipment. Features a fleet of accessories to meet individualized computing needs
- Easily moves through small doorways and over thresholds
- Use inside an office cubicle or small meeting space; compact design offers personalized video or computing
- Work sitting or standing with ergonomic 20" (51 cm) height-adjustment range
- Safe and neat routing of cables through the expansive cable management storage area
- Use a laptop or CPU for computing flexibility



COMPACT AND AGILE MOBILE DISPLAY HUB FOR TWO SCREENS OR ONE LARGER SCREEN

Widen your view—and move it too! Configure this compact, low-cost, height-adjustable cart to your needs: its flexible open architecture supports dual displays or a mid-size display, making it perfect for web conferencing or any other image-intensive mobile computing application. Select the dual-screen or the mid-sized screen cart and add the optional camera shelf as needed. The Neo-Flex WideView WorkSpace is designed for telemedicine, radiology, clinical PACS access, labs, manufacturing floors, distribution centers, distant-learning facilities, corporate settings and more.

- Durable, easy-to-clean exterior composed of aluminum, high-grade plastic and powder coated painted steel
- Four dual casters—lockable front casters
- Worksurface: 16.5" W x 14" D (42 x 36 cm)
- Wheel-to-wheel base dimensions: 17" x 20.5" (43 x 52 cm)
- Add the WideView Camera Shelf Kit (97-500-055) to place adjustable camera shelf above the display (order separately)
- Warranty: three (3) years



SAFE AND NEAT ROUTING OF CABLES THROUGH THE EXPANSIVE CABLE MANAGEMENT STORAGE AREAS

	Single	Dual
Part # (color)	24-189-055 (two-tone grey)	24-194-055 (two-tone grey)
Includes	Cart, LCD pivot, integrated worksurface/keyboard tray with left/right mouse tray, scanner holder bracket, mouse holder, rear handle, cable storage box, CPU holder, four dual casters (two locking)	Cart, crossbar with two (2) LCD mounts, integrated worksurface/keyboard tray with left/right mouse tray, scanner holder bracket, mouse holder, rear handle, cable storage box, CPU holder, four dual casters (two locking)
Typical LCD Size	≤ 42"	two ≤ 22"
<small>LCD SIZE IS APPROXIMATION. DIMENSION IS DIAGONAL MEASUREMENT OF SCREEN. LCD SIZE MAY BE EXCEEDED AS LONG AS SCREEN WEIGHT DOES NOT EXCEED MAXIMUM WEIGHT CAPACITY OF THE MOUNT.</small>		
Weight Capacity	16–50 lbs* (7,3–22,7 kg)	11–46 lbs* (5,0–20,9 kg)
Lift	20" (50,8 cm)	
Tilt	30°	— <small>INSTALL DUAL DISPLAYS AT 3.5° OR 8.5° UPWARD ANGLE FOR OPTIMIZED VIEWING CONDITIONS. DUAL DISPLAYS ARE NOT TILT ADJUSTABLE</small>
Rotation	90° P/L*	
VESA	MIS-D/E/F*	MIS-D*
Shipping Weight	82 lbs (37 kg)	
Shipping Dimensions	45.5"H x 19.75"W x 24"D (115,6 x 50,2 x 61 cm)	
Warranty	3 years	

*SEE WEBSITE FOR MORE INFORMATION



PT MURNI SOLUSINDO NUSANTARA
Digital Business Transformation Center

Branch Transformation | Customer Experience | Digital Teller Automation | Self-service Solution
Cash & Cheque Processing Solution | Digital Signage | RPA | Ergonomic Solution | Maintenance Service

 30+ YEARS OF EXPERIENCES	 TRUSTED BY MAJOR COMPANIES ACROSS SECTORS	 NATIONWIDE TECHNICAL SUPPORT WITH 100+ SERVICE POINTS AND 24/7 HELPDESK	 CORE COMPETENCY IN ERGONOMIC SOLUTIONS AND DIGITAL TRANSFORMATION SOLUTIONS	 SUPPORTED BY MORE THAN 700 DEDICATED STAFF AND TECHNICIANS
-------------------------------------	--	--	--	---

JAKARTA (Head Office & Multisector Simulation Room)

Jl. Lingkar Luar Barat No.1, +62-21 584 1060
 Jakarta Barat 11750, Indonesia +62-21 587 4505

BANDUNG +62-22 205 63705

SURABAYA +62-31 593 0010

MEDAN +62-61 453 2994

YOGYAKARTA +62-274 883 506

DENPASAR +62-361 499 323

SEMARANG +62-24 764 34391



1500 913 (Sales) 1500 013 (Helpdesk) info@murni.co.id PT Murni Solusindo Nusantara

ISO 9001:2015 Certified No. ID 14/02656

WWW.MURNI.CO.ID

©PT Murni Solusindo Nusantara. All products, images and brand names are trademarks and owned by respective company and are used for descriptive purpose only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purpose without prior notice.