

ergotron[®]

moving you forward

Neo-Flex[®] **Mobile MediaCenter**

- Move digital signage and images to where you need them
- Rotate your display to portrait or landscape orientation—no need to reinstall display
- Optional camera shelf accessory converts any space into a video-conference center
- Easily roll cart through standard-size doorways and over thresholds
- Patented Constant Force™ Technology enables smooth, effortless portrait-to-landscape rotation, tilt and height adjustment. Adjusts with just a touch—no knobs or levers
- Modular cable management channels conceal and organize cables
- Speedy assembly and installation



STRETCH YOUR DISPLAY MEDIA INVESTMENT WITH
LIFT, TILT, ROTATION—AND MOBILITY

Bring digital content to life with Ergotron's sleek Neo-Flex Mobile MediaCenter. With effortless height adjustment and integrated portrait-to-landscape capability, this cart stretches your investment by serving a variety of projection needs in rooms throughout a facility. Affordability, simple assembly and effortless operation make the Mobile MediaCenter perfect for digital signage, conferencing and other applications.



- Complies with UL Tip Standards 1667 and 1678
- Rugged plastic-composite shelf conveniently attaches to cart at any height
- Modular cable channel system is adaptable for various wiring configurations
- Portrait orientation is not recommended for some plasma displays. Contact display manufacturer if you have questions regarding your plasma's portrait-mode capability (this is not an issue with LCD technology)

- CPUs attach safely to rear of cart with Universal CPU Holder accessory (ordered separately). Compatible with CPU sizes from 12"H x 3"D to 18"H x 8.5"D (30 x 8 cm to 46 x 22 cm)

Small CPUs with VESA hole-mounting pattern can be mounted behind the display with the MMC VESA-CPU Mount (ordered separately); VESA-compliant (75/100 mm) thin client CPU must have either a 75 x 75 mm or 100 x 100 mm mounting hole pattern.

- Add the MMC Camera Shelf Kit (97-491-085, ordered separately) to place adjustable camera shelf above the display
- Three-year warranty



	LD	VHD	UHD
Part # (color)	24-190-085 (black)	24-191-085 (black)	24-192-085 (black)
Includes	Neo-Flex cart, display and pan assembly, lower main shelf, 4" (10 cm) casters (two locking), rear cable shelf, cable channel kit; videoconferencing equipment is not included		
Typical LCD Size	27-60"	37-75"	50-80"
<small>LCD SIZE IS APPROXIMATION. DIMENSION IS DIAGONAL MEASUREMENT OF SCREEN. LCD SIZE MAY BE EXCEEDED AS LONG AS SCREEN WEIGHT DOES NOT EXCEED MAXIMUM WEIGHT CAPACITY OF THE MOUNT.</small>			
Weight Capacity	25-50 lbs* (11,3-22,7 kg)	50-90 lbs* (22,7-40,8 kg)	90-120 lbs* (40,8-54,4 kg)
Lift	20" (50,8 cm)		
Tilt	20°		
Rotation	90°		
VESA	MIS-D/E/F*	MIS-D/F*	
Compatible Display(s)	See website		
Shipping Weight	101 lbs (46 kg)		
Shipping Dimensions	66"L x 20"H x 14"D (168 x 50,3 x 33,5 cm)		
Warranty	3 years		

*SEE WEBSITE FOR MORE INFORMATION



PT MURNI SOLUSINDO NUSANTARA
Digital Business Transformation Center

Branch Transformation | Customer Experience | Digital Teller Automation | Self-service Solution
Cash & Cheque Processing Solution | Digital Signage | RPA | Ergonomic Solution | Maintenance Service

 30+ YEARS OF EXPERIENCES	 TRUSTED BY MAJOR COMPANIES ACROSS SECTORS	 NATIONWIDE TECHNICAL SUPPORT WITH 100+ SERVICE POINTS AND 24/7 HELPDESK	 CORE COMPETENCY IN ERGONOMIC SOLUTIONS AND DIGITAL TRANSFORMATION SOLUTIONS	 SUPPORTED BY MORE THAN 700 DEDICATED STAFF AND TECHNICIANS
-------------------------------------	--	--	--	---

JAKARTA (Head Office & Multisector Simulation Room)

Jl. Lingkar Luar Barat No.1, +62-21 584 1060
Jakarta Barat 11750, Indonesia +62-21 587 4505

BANDUNG +62-22 205 63705

SURABAYA +62-31 593 0010

MEDAN +62-61 453 2994

YOGYAKARTA +62-274 883 506

DENPASAR +62-361 499 323

SEMARANG +62-24 764 34391



1500 913 (Sales) 1500 013 (Helpdesk) info@murni.co.id PT Murni Solusindo Nusantara

ISO 9001:2015 Certified No. ID 14/02656

WWW.MURNI.CO.ID

©PT Murni Solusindo Nusantara. All products, images and brand names are trademarks and owned by respective company and are used for descriptive purpose only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purpose without prior notice.