







IDP's new SOLID-510 is the next generation of its mid-range ID Card Printer platform. The SOLDI-510 inherits the most successful and proven elements of the SOLID-500 series -IDP's longest running ID Card Printer. Enhancements to the SOLID-510 include careful selection of highly reliable parts, the application of a new state-of-the art CPU and application specific features for unique projects.

The new SOLID-510 offers an upgrade path from single side printing (510S), to dual side printing (510D), and to dual side printing with lamination (510L). The SOLID-510L also uses IDP's patented Direct Lamination which is the industry's first adoption of direct lamination technology to drastically reduce heat-up time, save energy, and optimize the application of laminate to the card.

Performance - Essence of Card Printer

The core spirit of a card printer is its print quality, print speed and stability. IDP's new SOLID-510 card printer increases print speeds up to by 10%, enhances print quality by optimizing precise ribbon movement, and provides faster processing speed by utilizing a new powerful CPU.

Careful Consideration of User Convenience

From the initial design of the SOLID-510 Series, IDP has taken careful consideration of the end-user to create an easy to use and flexible card printer. The SOLID-510 offers a larger card loading capacity (up to 200 cards), a choice of output direction, new cartridge loading lamination, support of transparent magnetic cards, optional support of CR79 card and an optional all-in-one type lock system are all features of the new SOLID-510.

With a more advanced SOLID-510 from IDP, card issuance will be easier and more productive than ever before.



SOLID Applications ensure proper card issuance and data management with SOLID series printers at no extra cost.

- Design and Print (Images, Photos, Texts, etc.) 1D & 2D Barcode printing

- Auto portrait (Auto face detection & adjustment of size & position) Card design templates
- Plug-in for supporting external devices
 Convenient issuance of cards and data management

Magnetic stripe (MS), contact & contactless smart card encoding by using plug-in program



SOLID series provides effective security features for access control and data encryption.

SOLID series has a password verification function to provide administrator and user authentications.

SOLID series can set a specific authorized PC for encoding and printing cards.

SOLID series can encrypt data transmitted on USB and can support SSL (Secure Socket Layer) protocol on ethernet communications.



SOLID series can utilize the network printer server for encoding and printing cards.

encode MS, contact and contactless smart card through the network.

SOLID Ethernet module has OCP(Open Card Print) protocol which can encode and print cards by using commands on multiple platforms without installing the printer driver

Available encoding the contact & contactless smart card by Ethernet.



SPECIFICATIONS

PRINTING		SYSTEM			
 Print Type 	Dye-Sublimation	Memory	64MB RAM		
 Print Area 	Edge to Edge	 Display & Button 	2 Line LCD / 2 LED Buttons		
 Resolution 	300dpi (Color & Mono), 600 & 1200dpi (Mono only)	 Supported Platforms 	Microsoft Windows 7/ 8/ 10, Mac OS, Linux		
 Dual Sided Printing 	Dual Sided Printing	 Communication 	USB, Ethernet (Option)		
CARD		Power	Free Voltage (AC100/ 240V, 50~60Hz) / 48W		
		 Temperature/Humidity 	15~35℃ / 35~70%		
 Card Feeding Card Size 	Automatic ISO CR80 or ISO CR79 (Option-Factory installed)	 Security 	Physical Lock & Kensington Lock (Option)		
Card Thickness	0,38mm (15mil), 1,0mm (40mil)	DIMENSIONS / WEIGHT			
 Card Type 	PVC, PET, Composite PVC	• Millimeter (WxLxH)	165 x 498 x 210		
PRINT SPEED		 Inch (WxLxH) 	6.5 x 19.6 x 8.3		
Monochrome	5 sec./card (720 cards/hour)	• Kg/lbs	5.2 / 11.5		
YMCKO	Front-in & Front-out : Max. 17 sec./card (212 cards/hour)	ENCODING OPTIONS			
	Front-in & Back-out : Max, 16 sec /card (225 cards/hour)	 Magnetic 	ISO7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II		
 YMCKOK 	Max, 22 sec./card (164 cards/hour)	 Contact 	ISO 7816 (ID-1)		
	,	 Contactless 	MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS		
CAPACITY		CERTIFICATIONS			
 Input Hopper 	100 cards / 200 cards with cover open				
 Output Hopper 	Front: 40 cards / Back: 100 cards (Optional Back-side Stacker)	CB (E F© @ 🕅			
FEATURES					



CONSUMABLES

d : May change under specific o

YMCKO	250 Cards/Roll	Full Color Ribbon with Resin Black & Overlay	YMCFKO	200 Cards/Roll	Full Color Ribbon with UV Panel, Resin Black and Overlay
үмскок	200 Cards/Roll	Full Color Ribbon with Resin Black, Overlay & Black for Back Side	НҮМСКО	350 Cards/Roll	Half Panel Size Color Ribbon with Resin Black and Overlay

MON) RIBBONS					SECU	rity films
ко	600 Cards/Roll	Black with Overlay	R	1200 Cards/Roll	Red	HPF	250 Cards/
К	1200 Cards/Roll	Black	MG	1200 Cards/Roll	Metallic Gold	CPF	250 Cards/
W	1200 Cards/Roll	White	MS	1200 Cards/Roll	Metallic Sliver		
В	1200 Cards/Roll	Blue	SO	1200 Cards/Roll	Scratch-Off	_	

Hologram Patch Film

Clear Patch Film

250 Cards/Roll

250 Cards/Roll

PT MURNI SOLUSINDO NUSANTARA Branch Transformation Customer Experience Digital Teller Automation Self-service Solution Digital Business Transformation Center Cash & Cheque Processing Solution Digital Signage RPA Ergonomic Solution Maintenance Service							
30+ YEARS OF EXPERIENCES	TRUSTED BY MAJOR COMPANIES ACROSS SECTORS	NATIONWIDE TECHNICAL SUPPORT WITH 100+ SERVICE POINTS AND 24/7 HELPDESK		OFFIC	DEPENCY IN E/BANKING UIPMENT DNSUMABLES	SUPPORTED BY MORE THAN 700 DEDICATED STAFF AND TECHNICIANS	
JAKARTA (Head Office & Mult Jl. Lingkar Luar Barat No.1, Jakarta Barat 11750, Indonesia (\$1500 913 (Sales) (\$1500 01	 +62-21 584 1060 +62-21 587 4505 	BANDUNG SURABAYA MEDAN p.id in Off	+62-22 205 63705 +62-31 593 0010 +62-61 453 2994	YOGYAKARTA DENPASAR SEMARANG usindo Nusanta	+62-274 883 506 +62-361 499 323 +62-24 764 34391 ara ISO 900	D1:2015 Certified No. ID 14/02656	

WWW.MURNI.CO.ID Control Solusindo Nusantara. All products, images and brand names are trademarks and owned by respective company and are used for descriptive purpose only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purpose without prior notice.