

Elo PayPoint® Plus for Android™

All-In-One POS Platform





Plug & Play



Industry Standard Peripherals



Product Overview

PayPoint Plus for Android is an all-in-one mPOS solution that brings simplicity and elegance to the point of sale with powerful Qualcomm® Snapdragon™ processing and an Android 7.1 Nougat OS. Offering sleek, modern style with peripherals built in, PayPoint Plus for Android integrates a 15.6-inch TouchPro™ PCAP touchscreen, 3-inch Star receipt printer, industry standard 16-inch cash drawer, Magtek MSR, Honeywell 2D barcode scanner and a customer facing display*. 3rd party peripherals can also be added through one of the many I/O connections, allowing for an EMV payment terminal, second cash drawer or scale if needed.

PayPoint transforms traditional POS into a beautiful and functional space-saving solution to help you to better serve your customers. The flip-for-signature screen encourages shopper engagement and electronic receipt delivery. And, with its single cable design, PayPoint makes setting up the point of sale system fast and easy - just unbox, plug in, connect, and go.

Deploy your POS software on a stylish all-in-one platform with the ease of a single cable for installation

Remotely manage your device and deploy your content on PayPoint with EloView®

Increase speed at checkout with powerful processor, upgraded memory and Wi-Fi/BT connectivity

Elo PayPoint® Plus for Android™

Specifications	No.			
Color	White			
Processor	Qualcomm Snapdragon Octa Core 2.0GHz			
Memory (RAM)	3GB on board memory			
Storage	32GB SSD			
Ethernet Port	1 x LAN RJ45 (Gigabit)			
Wireless	802.11 b/g/n/ac; Bluetooth: 4.1			
I/O Ports	4 x Type A USB 2.0, 1 x mini USB 2.0, 2 x RJ45 serial, 1 x micro HDMI, 1 x 12V power USB, 1 x RJ12 cash drawer			
Operating System	Android 7.1 with EloView (device management and content deployment platform) Star TSP100III USB (thermal printer), 3" (80mm) receipt printer with auto-cutter, maximum paper roll diameter 80mm, speed 250mm/sec			
Printer				
Barcode Scanner	Honeywell N3680 1D/2D barcode scanner, CMOS sensor with 640 x 480 pixel resolution Supported symbologies: - Linear: Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data bar - 2D Stacked: Codablock A, Codablock F, PDF417, MicroPDF417 - 2D Matrix: Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin) code - Postal Codes: Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet			
Cash Drawer	Outer dimensions: 16.18" x 16.54" x 3.50" / 411mm x 420mm x 89mm Removable till insert, media slot for checks, 3 position lock NA/China Models: 5 bill, 6 coin / Worldwide Models: 4 bill, 8 coin			
MSR	Magtek 3-track encryptable**, default security level 2 with remote key injection through Magensa			
Customer Facing Display*	2 line, 16 character display			
Display	15.6" diagonal, Active matrix TFT LCD (LED), 16x9			
Useful Screen Area (W x H)	13.54" x 7.64" / 344mm x 194mm			
Native (optimal) Resolution	Full HD 1920 x 1080 @ 60Hz			
Touch Technology	TouchPro Pro-G (Glass) PCAP			
Number of Touches	5			
Brightness (typical)	LCD panel: 300 nits; PCAP: 260 nits			
Response Time-total (typical)	30 msec			
Viewing Angle (typical)	Horizontal: ± 85° or 170° total / Vertical: ± 85° or 170° total			
Contrast Ratio (typical)	800:1			
Power	Internal power supply; AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz; Max Power Consumption: 92W			
Speakers	1x 1W internal speakers			
Dimensions	16.2" x 12.6" x 16.2" / 420mm x 411mm x 321mm			
Weight	Unpackaged: 19.84 lbs / 9 kg; Packaged: 29.76 lbs / 13.5 kg			
Shipping Box Dimensions	25.5" x 21.6" x 19.1" / 648mm x 548mm x 484mm			
Mounting Options	Ability to secure base to tabletop			
Real-Time Clock	Replaceable lithium coin cell battery for clock			
Temperature	Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)			
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%			
Warranty	3 years			
Regulatory Approvals and Declarations	UL/cUL, FCC, CE, CB, CCC, SRRC, VCCI, MIC, RCM			
What's in the Box	PayPoint Plus for Android, power cable, 1 receipt paper roll, 2 cash drawer keys, Quick Install Guide, RJ45 to DB9 serial cable			

^{*}Included on NA/China models only

Ordering Information

Part Number	Display	Color	os	Availability	Peripherals
E347513	15.6" TouchPro PCAP	White	Android 7.1	North America/China	3" printer, 2D scanner, MSR, CFD, 5x6 cash drawer
E347918	15.6" TouchPro PCAP	White	Android 7.1	Worldwide	3" printer, 2D scanner, MSR, 4x8 cash drawer

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

North America Tel +1 408 597 8000 Fax +1 408 597 8050 elosales.na@elotouch.com **Europe**Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-PacificTel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America Tel +52 55 2281 6958 elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and PayPoint are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17111AES00092



^{**}Encryption key and verification of encryption is customer responsibility