

Banknote Binding Machine with Printer

Mabas SBM-95



Equipped with built-in inkjet printer for information printing and pusher function that automatically ejects banded notes without Operator's assistance, MABAS SBM-95 greatly improved efficiency & productivity to speed up business process.

Why This Product Is Different?



Save Time & Efforts

with automatic pusher function that will push banded banknotes away from the banding area, allowing for uninterrupted & continuous processing



Improved Traceability

with fully customizable information printing on banding paper, including company names, denomination, time & date, Operator's name, and location



Cost-Efficient yet Long-Lasting Printing

With long banding paper & inkjet endorsement printer that increase endorsement lifetime



Tight & Highly Durable Banding

for banknotes in various fitness level, even without the need to bend the banknotes for tighter banding results

How This Product Benefits Me



Long-Term Investment

with highly durable construction made of metal parts for up to 10 years of usage



Improved Staff Performance & Productivity

with its automatic functions & high quality banding results



Improved Security

by easily tracing the origin of bundled banknotes through information printed on the banding paper in case of amount discrepancy



Ready to Use Products

with its simple operation & user-friendly menu

Technical Specifications

Parameter	Measure
DIMENSION	400 X 112 X 245 MM (W X D X H)
DOCUMENT SIZE	HEIGHT : 60-90 MM WIDTH : 90 MM OR MORE BUNDLE THICKNESS : 25 MM (MAX)
PROCESSING SPEED	WITH AUTO-EJECT AND PRINTING : 12 - 15 CYCLES/MINUTE WITHOUT AUTO-EJECT AND PRINTING : 18 - 20 CYCLES/MINUTE
CAPACITY	HOPPER: 200* NOTES (MAX) *MAXIMUM NUMBER OF BANDED NOTES AS LONG AS THE THICKNESS DOES NOT EXCEED 25 MM.
PRINTER CARTRIDGE	1 CARTRIDGE HP 51645 A (42 ML) = UP TO APPROX. 6.5 PAPER ROLLS (APPROX. 4,225 BANDINGS WITH 4 LINES PRINTING)
DISPLAY	LCD DISPLAY 16 CHARACTERS X 2 LINES (SHOWING MACHINE SETTINGS, OPERATOR, MACHINE STATUS, HEATER'S TEMPERATURE, TOTAL BANDING COUNT, ACTIVE SENSORS, ETC.)
TEMPERATURE OF HEATER	180 - 250 ° C
WEIGHT	11 KG
POWER CONSUMPTION	OPERATION : DC 24V, 80 W STANDBY : 5W
WELDING TEMPERATURE	ADJUSTABLE
BAND TIGHTNESS	ADJUSTABLE
BANDING PAPER	REEL INNER DIAMETER : STANDARD : 50 MM CUSTOM : 76 MM REEL OUTER DIAMETER : STANDARD : 170 MM CUSTOM : 360 MM PAPER BAND WIDTH : MAX. 40 MM PAPER BAND MATERIAL : PE-COATED PAPER

Related Solutions



Plus P-413

A semi-automatic & multi-purpose banknote strapping machine to strap banknotes or other large size documents



CCE M2000

Cost-effective vacuum banknotes counter, suitable for front-office or back-office operation



DORS 50

The classic and ultra-light UV counterfeit detector



PT MURNI SOLUSINDO NUSANTARA
Digital Business Transformation Center

Branch Transformation | Customer Experience | Digital Teller Automation | Self-service Solution
Cash & Cheque Processing Solution | Digital Signage | RPA | Ergonomic Solution | Maintenance Service



30+ YEARS
OF EXPERIENCES



TRUSTED BY
MAJOR COMPANIES
ACROSS SECTORS



NATIONWIDE
TECHNICAL SUPPORT
WITH 100+ SERVICE POINTS
AND 24/7 HELPDESK



CORE COMPETENCY IN
CASH PROCESSING AND
DIGITAL TRANSFORMATION
SOLUTIONS



SUPPORTED BY MORE THAN
700 DEDICATED STAFF
AND TECHNICIANS

JAKARTA (Head Office & Multisector Simulation Room)

Jl. Lingkar Luar Barat No.1, +62-21 584 1060
Jakarta Barat 11750, Indonesia +62-21 587 4505

BANDUNG +62-22 205 63705

SURABAYA +62-31 593 0010

MEDAN +62-61 453 2994

YOGYAKARTA +62-274 883 506

DENPASAR +62-361 499 323

SEMARANG +62-24 764 34391



1500 913 (Sales) 1500 013 (Helpdesk) info@murni.co.id PT Murni Solusindo Nusantara

ISO 9001:2015 Certified No. ID 14/02656

WWW.MURNI.CO.ID

©PT Murni Solusindo Nusantara. All products, images and brand names are trademarks and owned by respective company and are used for descriptive purpose only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purpose without prior notice.